

Presenting the . . .

Jackson Vertical Edger



- See-thru design with individual sawdust chutes provides unparalleled visibility.
- Heavy, rigid formed steel frame with built-in top C-face motor mount. (V-belt drive from the bottom is also available).
- Dual-keyed 2-7/16" arbor with brass-sleeved steel collars is standard, splined arbor is also available.
- Self-aligning bearings are mounted in heavy precision-machined steel housings.
- Available with straight hydraulic, electric/hydraulic, electronic logic, or full computer controls.

Jackson Lumber Harvester Co., Inc.
830 North State Road 37
Mondovi WI 54755 USA
Phone: 1-715-926-3816
FAX: 1-715-926-4545

Where Ideas Are In Production
Jackson
LUMBER HARVESTER
COMPANY, INCORPORATED

Jackson Vertical Edger Specifications

Number Of Saws.....	2 or 3
Over-all Size.....	66" High x 35" Wide x 24" Deep
Approximate Weight.....	950 Lbs
Saw Speed	1750 RPM
Saw Diameter	20"
Saw Collars	Brass-sleeved Steel
Collar Bearings	Self-aligning 2-7/16" Inserts
Saw Arbor.....	Double-keyed 2-7/16", Splined Arbor optional
Maximum Cutting Depth	6"
Maximum Passable Depth	8"
Maximum Cutting Width.....	23"
Minimum Cutting Width.....	4"
Type Of Control.....	Manual Hydraulic, Electric/Hydraulic or Electronic/Hydraulic optional
Drive System	40 HP Electric Motor, V-Belt / Gearbox optional