

Unit		16D4H	30D6H	30D6HL	30D10H	30D10HL	36D10H	36D10HL		
Allowable Wood Size	Diameter	2" - 12" (50 - 38 mm)	2" - 26" (50 - 660 mm)			2" - 32" (50 - 840 mm)				
	Length	3'0" - 4'6" (0,90 - 1,35 m)	3'0" - 4'6" (0,90 - 1,35 m)	7'0" - 8'6" (2,13 - 2,60 m)	3'0" - 4'6" (0,90 - 1,35 m)	7'0" - 8'6" (2,13 - 2,60 m)	3'0" - 4'6" (0,90 - 1,35 m)	7'0" - 8'6" (2,13 - 2,60 m)		
Cutter heads	Diameter	4" (102 mm)	6" (152 mm)		10" (254 mm)		10" (254 mm)			
	Knives	3 each, 16" (406 mm) long	4 each, 27-3/4" (705 mm) long		8 each, 27-3/4" (705 mm) long		8 each, 33-3/4" (857 mm) long			
Rated output per hour		4.5 - 9.8 yd ³ (3,4 - 7,5 m ³)	9.3 - 20.2 yd ³ (7,1 - 15,4 m ³)		20.7 - 45.2 yd ³ (15,8 - 34,6 m ³)		25.6 - 68.3 yd ³ (19,6 - 52,2 m ³)			
Cutter heads drive	Electric motor	30 HP (22 kW)	50 HP (37 kW)	50 HP (37 kW)	75 HP (56 kW)	75 HP (56 kW)	100 HP (75 kW)	100 HP (75 kW)		
	PTO (net)	45 HP (34 kW)	65 HP (48 kW)	75 HP (56 kW)	90 HP (67 kW)	100 HP (75 kW)	115 HP (86 kW)	125 HP (93 kW)		
	Engine	80 HP (60 kW)	87 HP (65 kW)	100 HP (75 kW)	120 HP (89 kW)	134 HP (100 kW)	153 HP (115 kW)	167 HP (125 kW)		
Hopper box drive	Electric motor	15 HP (11 kW)	15 HP (11 kW)	25 HP (18 kW)	15 HP (11 kW)	25 HP (18 kW)	15 HP (11 kW)	25 HP (18 kW)		
	PTO or engine	Hydraulic pump driven from cutter heads drive								
Overall size, shipping	Frame	Length	15'10" (4,80 m)	15'10" (4,80 m)	24'4" (7,40 m)	15'10" (4,80 m)	24'4" (7,40 m)	15'10" (4,80 m)	24'4" (7,40 m)	
		Width	5'0" (1,50 m)	6'5" (1,95 m)		6'9" (2,06 m)		7'6" (2,30 m)		
		Height	7'2" (2,20 m)							
	Hopper box	Length	7'4" (2,24 m)	7'4" (2,24 m)	11'6" (3,50 m)	7'4" (2,24 m)	11'6" (3,50 m)	7'4" (2,24 m)	11'6" (3,50 m)	
		Width	2'1" (0,64 m)	3'0" (0,91 m)					3'6" (1,07 m)	
		Height	4'2" (1,27 m)							
	Hydraulic power system	Length	5'4" (1,63 m)							
		Width	2'5" (0,74 m)							
		Height	4'9" (1,45 m)							
Overall size, installed	Mill	Length	15'10" (4,80 m)	15'10" (4,80 m)	24'4" (7,40 m)	15'10" (4,80 m)	24'4" (7,40 m)	15'10" (4,80 m)	24'4" (7,40 m)	
		Width	5'0" (1,50 m)	6'5" (1,95 m)		6'9" (2,06 m)		7'6" (2,30 m)		
		Height	8'11" (2,72 m)							
	Hydraulic power system	Length	5'4" (1,63 m)							
		Width	2'5" (0,74 m)							
		Height	4'9" (1,45 m)							
Approx. weight		6,000 lbs (2.700 kg)	10,000 lbs (4.500 kg)	13,000 lbs (5.900 kg)	12,000 lbs (5.400 kg)	14,000 lbs (6.350 kg)	13,000 lbs (5.900 kg)	15,000 lbs (6.800 kg)		
Printable brochure		16D4H	30D6H	30D6HL	30D10H	30D10HL		36D10HL		
Video		16D4	30D6H		30D10H	30D10HL		36D10HL		

(Please note that these specifications may change without notice.)
[Click here to download this chart in PDF format.](#)